



## **SPECIFICATIONS**























## 919Va2 19" TFT MONITOR

Panel	19" (48 cm) TFT Active Matrix LCD
Design Line	Value
Pixel / Dot Pitch	0.294 mm x 0.294 mm
Viewable Image Size (Diagonal)	
Display Area	376 mm x 301 mm
Brightness	300 cd/m² (typ)
Contrast Ratio	10000:1 (DCR)
Typ. Response Time (tr+tf)	2 ms (GtG)
Viewing Angle H / V	Horizontal: 170 Degrees
	Vertical: 160 Degrees
Compatibility	VESA, XGA, VGA, SVGA, SXGA, Mac, Equipped With VGA Port
Scanning Frequency	Horizontal: 30–80 KHz
	Vertical: 55–75 KHz
Pixel Frequency	135 MHz
Maximum Resolution	1280 x 1024@75Hz
Recommended Resolution	1280 x 1024@75Hz
Resolution Supported	640x480@60/ 67/ 72/75Hz, 800x 600@56/ 60/ 72/ 75Hz
	1024x768@60/ 70/ 72/ 75Hz, 1280x1024@60/ 75Hz
Colours	16,7M
Signal Input	Analogue: D-Sub
	Digital Input: DVI-D
Connectors	Analogue RGB Signal: 15-pin D-sub
	DVI-D: 24-pin DVI-D
Power Source	100~240VAC, 50/60Hz
Power Consumption	DDC 1/2B/CI or VESA DDC2B TM
Power Consumption	
Plug & Play	YES
EPA ENERGY STAR ®	YES
User Control Function	AUTO, Menu, Power, Eco/Up, Down
runction	Brightness, Contrast, Eco Mode, Gamma (1,2,3), DCR, Clock,
	H/V Position, Color Temp, Color Boost, Pictures Boost, OSD Setup,
COR Lawrence	Auto Config, Reset, Information
OSD Languages	9 Languages
Speaker	2 x 1 Watt
Emissions Standard	
	TC006
Regulation	TC006  cUL, FCC, CE, TUV-bauart, EPA, IS013406-2, Vista premium, GOST,
Regulation	
	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST,
Other Features	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST, RoHS, Pixel Fault Class II  VESA 100 mmWall Mountable, Kensington Security Slot, 5-20° Tilt,
Other Features  Dimensions (WxHxD)	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST, RoHS, Pixel Fault Class II  VESA 100 mmWall Mountable, Kensington Security Slot, 5-20° Tilt,  Monitor: 409 x 409,5 x 210 mmm
Other Features  Dimensions (WxHxD)  Weight	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST, RoHS, Pixel Fault Class II  VESA 100 mmWall Mountable, Kensington Security Slot, 5-20° Tilt,
Regulation  Other Features  Dimensions (WxHxD)  Weight  Loading Qty w/pallet	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST, RoHS, Pixel Fault Class II  VESA 100 mmWall Mountable, Kensington Security Slot, 5-20° Tilt,  Monitor: 409 x 409,5 x 210 mmm
Other Features  Dimensions (WxHxD)  Weight	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST, RoHS, Pixel Fault Class II  VESA 100 mmWall Mountable, Kensington Security Slot, 5-20° Tilt,  Monitor: 409 x 409,5 x 210 mmm  Net: 3,85kg/ Gross: 5,4kg
Other Features  Dimensions (WxHxD)  Weight	cUL, FCC, CE, TUV-bauart, EPA, ISO13406-2, Vista premium, GOST, RoHS, Pixel Fault Class II  VESA 100 mmWall Mountable, Kensington Security Slot, 5-20° Tilt,  Monitor: 409 x 409,5 x 210 mmm  Net: 3,85kg/ Gross: 5,4kg  40° 2125 pcs